

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

### 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**
- **Article number: SM-202**
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GSI EUROPE - Import + Export GmbH  
Louise-Dumont-Str. 31  
40211 DÜSSELDORF  
GERMANY
- **Further information obtainable from:** Hobby Department
- **Emergency telephone number:** During normal opening times: +49/211/1665 98420

### 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225

Highly flammable liquid and vapour.



corrosion

Eye Dam. 1 H318

Causes serious eye damage.



Skin Irrit. 2 H315

Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS05



GHS07

(Contd. on page 2)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
butan-1-ol  
4-methylpentan-2-one  
ethyl acetate  
butanone
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335, EUH066	>25–≤50%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	>25–≤50%
CAS: 78-93-3 EINECS: 201-159-0	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥20–≤25%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥3–<10%

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**

(Contd. of page 2)

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	>2.5–≤10%
CAS: 5131-66-8 EINECS: 225-878-4	3-butoxypropan-2-ol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	>2.5–<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**

See Section 13 for disposal information.

(Contd. of page 3)

## 7 Handling and storage

- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

### 108-10-1 4-methylpentan-2-one

WEL	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm Sk, BMGV
-----	--

### 141-78-6 ethyl acetate

WEL	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
-----	--

### 78-93-3 butanone

WEL	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV
-----	---

### 71-36-3 butan-1-ol

WEL	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

### 123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
-----	---

(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

<b>Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2</b>
---

(Contd. of page 4)

<b>· Ingredients with biological limit values:</b>	
--	--

<b>108-10-1 4-methylpentan-2-one</b>	
--------------------------------------	--

BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
------	--

<b>78-93-3 butanone</b>	
-------------------------	--

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

-GB-

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2

(Contd. of page 5)

## · Eye/face protection



Tightly sealed goggles

## 9 Physical and chemical properties

## · Information on basic physical and chemical properties

## · General Information

· Physical state	Fluid
· Colour:	metallisch
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	76.5 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.1 Vol % (108-10-1 4-methylpentan-2-one)
· Upper:	11.5 Vol % (141-78-6 ethyl acetate)
· Flash point:	2.6 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	120 hPa
· Density and/or relative density	
· Density at 20 °C:	0.8–1 g/cm <sup>3</sup>
· Relative density	Not determined.
· Bulk density:	800–1,000 kg/m <sup>3</sup>
· Vapour density	Not determined.

## · Other information

## · Appearance:

· Form: Fluid

## · Important information on protection of health and environment, and on safety.

## · Ignition temperature:

260 °C

## · Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 7)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**

(Contd. of page 6)

- |                              |                 |
|------------------------------|-----------------|
| · <b>Solvent content:</b>    |                 |
| · <b>Organic solvents:</b>   | 90.0 %          |
| · <b>VOC (EC)</b>            | 90.00 %         |
| · <b>Change in condition</b> |                 |
| · <b>Evaporation rate</b>    | Not determined. |

· **Information with regard to physical hazard classes**

- |  |                                     |
|--|-------------------------------------|
| · <b>Explosives</b>  | Void                                |
| · <b>Flammable gases</b>   | Void                                |
| · <b>Aerosols</b>  | Void                                |
| · <b>Oxidising gases</b>   | Void                                |
| · <b>Gases under pressure</b>  | Void                                |
| · <b>Flammable liquids</b>   | Highly flammable liquid and vapour. |
| · <b>Flammable solids</b>  | Void                                |
| · <b>Self-reactive substances and mixtures</b>                                     | Void                                |
| · <b>Pyrophoric liquids</b>  | Void                                |
| · <b>Pyrophoric solids</b>   | Void                                |
| · <b>Self-heating substances and mixtures</b>                                      | Void                                |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void                                |
| · <b>Oxidising liquids</b>   | Void                                |
| · <b>Oxidising solids</b>  | Void                                |
| · <b>Organic peroxides</b>   | Void                                |
| · <b>Corrosive to metals</b>   | Void                                |
| · <b>Desensitised explosives</b>   | Void                                |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

- GB -

(Contd. on page 8)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2

(Contd. of page 7)

### 11 Toxicological information

- Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

- LD/LC50 values relevant for classification:

#### ATE (Acute Toxicity Estimates)

Oral	LD50	15,800 mg/kg (rat)
Inhalative	LC50/4 h	27.7–55.3 mg/l (rat)

#### 108-10-1 4-methylpentan-2-one

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	8.3–16.6 mg/l (rat)

#### 141-78-6 ethyl acetate

Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)

#### 78-93-3 butanone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

#### 71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

#### 123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- Information on other hazards

- Endocrine disrupting properties

78-93-3	butanone	List II
---------	----------	---------

### 12 Ecological information

- Toxicity
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 9)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**


(Contd. of page 8)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
 Must not reach sewage water or drainage ditch undiluted or unneutralised.  
 Danger to drinking water if even extremely small quantities leak into the ground.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### 14 Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>UN number or ID number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | UN1993   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>  | 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHYL METHYL KETONE (METHYL ETHYL KETONE))<br><br>FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHYL METHYL KETONE (METHYL ETHYL KETONE))<br><br>Flammable liquid, n.o.s. (ETHYL ACETATE, ETHYL METHYL KETONE (METHYL ETHYL KETONE)) |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   |  |
| <div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> | 3 Flammable liquids.<br>3  |

(Contd. on page 10)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**

(Contd. of page 9)

· <b>Packing group</b>	II
· <b>ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Flammable liquids.
· <b>Hazard identification number (Kemler code):</b>	33
· <b>EMS Number:</b>	F-E, <u>S-E</u>
· <b>Stowage Category</b>	B
· <b>Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
-----	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D/E
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHYL METHYL KETONE (METHYL ETHYL KETONE)), 3, II

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 1.0

Revision: 21.02.2022

**Trade name: Mr. COLOR SUPER METALLIC II - SUPER GOLD 2**

(Contd. of page 10)

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** Hobby Department

- **Contact:** -

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB